

**ACRYL FILLER 5+1 HS Q-2002****SECTION 1: SUBSTANCE/MIXTURE IDENTIFICATION AND MANUFACTURER/SUPPLIER IDENTIFICATION****1.1. Product identification****ACRYL FILLER 5+1 HS Q-2002****1.2. Relevant identified uses of the substance or mixture and uses advised against**

Acryl filler (component A) to be applied with a spray gun. For professional use in car refinsh.

1.3. Data of the safety data sheet supplier**Przedsiębiorstwo RANAL Sp. z o.o.**

Ul. Warszawska 36a
PL 42-240 Rudniki
Tel: +48 34 329-45-03
Fax: +48 34 320-12-16

Person responsible for the safety data sheet

e-mail: ranal@ranal.pl

1.4. Emergency telephone

+48 34 329-45-03 (from 7:30 am. to 3:30 pm.)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture****Classification 1999/45/WE:**

The mixture was classified as dangerous according to current regulations – see section 15.
Harmful product. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking. Flammable.

2.2. Label elements:

Contains: xylene

Signs:



Risk symbol:

Xn Harmful

Risk index:

R10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R66 Repeated exposure may cause skin dryness or cracking.

Safety index:

S(2-) Keep out of the reach of children.
S23 Do not breathe vapour/spray.
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S38 In case of insufficient ventilation wear suitable respiratory equipment.
S46 If swallowed, seek medical advice immediately and show this container or label.

2.3. Other hazards

No data available.



ACRYL FILLER 5+1 HS Q-2002

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable.

3.2. Mixtures

Product identification

ACRYL FILLER 5+1 HS Q-2002

Substance name	Identification numbers	Classification and marking	Concentration [%]
Xylene	EC: 215-535-7 CAS: 1330-20-7 Index no: 601-022-00-9 Registration no: --	Classification 67/548/EEC: R10, Xn; R20/21 Xi; R38 Classification 1272/2008/EC: Flam. Liq. 3; H226; Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit.2; H315	5-15%
Butyl acetate	EC: 204-658-1 CAS: 123-86-4 Index no: 607-025-00-1 Registration no: --	Classification 67/548/EEC: R10, R66-67 Classification 1272/2008/EC: Flam. Liq. 3; H226; STOT SE 3; H336	5-10%
1-metoxy –2-propanol acetate	EC: 203-603-9 CAS: 108-65-6 Index no: 607-195-00-7 Registration no: --	Classification 67/548/EEC: R10 Classification 1272/2008/EC: Flam. Liq. 3; H226;	5-10%

Full text of the phrases identifying the types of hazard and R phrases provided in section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures:

General information:

See section 11 of the Material Safety Data Sheet.

Inhalation:

Take the victim outside to the fresh air, ensure quiet surrounding, in case of no breath ensure artificial respiration. **Call a doctor.**

Skin:

Take off contaminated clothing. Rinse contaminated skin with plenty of lukewarm water for about 15 min. If irritation persists consult a doctor.

Eyes:

Rinse immediately with plenty of water for about 15 min, avoid strong water jet- risk of cornea damage, consult a doctor.

Alimentary tract:

Do not cause vomiting (choking risk). Rinse mouth with water. If conscious, administer 1-2 glasses of warm

**ACRYL FILLER 5+1 HS Q-2002**

water. Call a doctor. Person giving first aid should wear medical gloves.

4.2. Most important symptoms both acute and delayed

Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indications of any immediate medical attention and special treatment needed

Special measures allowing for specialist and immediate aid should be available in the place of work.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

Powder, foam resistant to alcohols, carbon dioxide, water mist.

5.2. Special hazards arising from the substance or mixture

Carbon monoxide and other toxic gases may be generated in case of fire.

5.3. Advice for firefighters

Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water from a safe distance.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency measures**

For persons not being members of aid giving staff:

Remove ignition sources. Ensure sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal safety measures – see section 8 of Material Safety Data Sheet.

For persons being the members of aid giving staff:

Persons giving aid should wear protective clothing made of coated impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber.

6.2. Environmental precautions

Prevent leakage to the sewage system, surface waters, underground waters and soil.

6.3. Methods and materials for containment and cleaning up.

Stop the leakage (close the liquid inflow, seal), place damaged container in an emergency container, remove the liquid mechanically and place it in an emergency container. In case of large leakage embank the area. In case of small amounts, collect with the use of a binding agent (e.g. mica, diatomaceous earth, sand).

6.4. Reference to other sections

Personal protection measures– see section 8 of the Material Safety Data Sheet. Disposal considerations – see section 13 of the Material Safety Data Sheet.

SECTION 7: HANDLING AND STORAGE OF SUBSTANCES AND MIXTURES**7.1. Precautions for safe handling**

Keep away from heat and sources of ignition. Prevent leakage to the sewage system, surface waters, underground waters and soil. Use only in well ventilated rooms. Do not smoke. Do not inhale vapours. Avoid contact with skin and eyes. Take precaution measures against electrostatic discharge. Use personal protection measures – see section 8 of the Material Safety Data Sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in well sealed original containers. Do not store near large amounts of organic peroxides or other strong oxidants. Take precaution measures against electrostatic discharge. Store in cool, well-ventilated rooms. Protect from the sunrays, heat sources and low temperatures.

7.3. Special end use(s)

Acryl filler (component A) to be applied with a spray gun. For professional use in car body refinish taking into consideration the information included in subsections 7.1 and 7.2.



ACRYL FILLER 5+1 HS Q-2002

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION MEASURES

8.1. Control parameters

CAS NUMBER:	SUBSTANCE	MPC (mg/m ³)	MPIC (mg/m ³)	MPCC (mg/m ³)
1330-20-7	Xylene	100	---	---
123-86-4	Butyl acetate	200	950	---
108-65-6	1-methoxy -2-propanol acetate	260	520	---

Krajowe dopuszczalne wartości biologiczne:

NUMER CAS:	SUBSTANCE ABSORBED	SUBSTANCE MARKED	BIOLOGICAL MATERIAL	PCB VALUES
1330-20-7	Xylene	ethyl hippuric acid	urine*	0,75 g/g creatinine

Notice: * single sample, taken at the end of a daily exposure any day.

8.2. Exposure control

Respiratory tract protection:

Gas mask with A type absorber (EN 141).

Hand protection:

Protective gloves PN-EN 374-3 (viton, 0,7 mm thick, penetration time > 480 min, nitril rubber, 0,4 mm thick, penetration time > 30 min).

Eye protection:

Tight protective glasses.

Skin protection:

Proper protective clothing (coated, impregnated fabrics).

Workplace:

Fixed fume extraction and general ventilation.

Environmental exposure control:

Prevent leakage to the sewage system, surface waters, underground waters and soil.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Parameter	Value
Physical state	liquid
Colour	according to specification
Odour	strong, powerful
Odour treshold	0.9-9 mg/m ³ (xylene)
pH	not applicable
Melting / freezing point	not applicable
Boiling point	126-145°C
Flash point	24°C
Autoignition point	about 270-300°C
Breakdown point	not specified
Evaporation rate	not specified
Flammability (solid, gas)	not applicable
Explosion limits	% bottom: 1.1 vol% top: 8.0 vol% (xylene)
Vapour pressure	13 hPa (20°C) (butyl acetate)
Vapour density(with regard to air)	4.0 (butyl acetate)
Density	about 1.6 g/cm ³ (20°C)
Solubility (in water)	poor
n-oktanol/water division ratio	1,85 (butyl acetate)

**ACRYL FILLER 5+1 HS Q-2002**

Viscosity	5000 – 10000 mPas
Explosive properties	not applicable
Oxidizing properties	not applicable

9.2. Other information

No data available

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Product not reactive under normal conditions.

10.2. Chemical stability

Product stabile under normal conditions.

10.3. Possibility of hazardous reactions

Carbon monoxide and other toxic gases may be generated as a result of thermal decomposition.

10.4. Conditions to be avoided

Flammable product. Avoid contact with strong oxidants, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from the influence of sunrays and heat sources.

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases, as well as other strong oxidants.

10.6. Hazardous decomposition products

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

No experimental data available on the preparation. Evaluation based on the data on dangerous ingredients included in the preparation.

a) Acute toxicity

Xylene

LD₅₀ (rat, ingestion) 5000 mg/kg
LC₅₀ (rat, inhalation) 4550 ppm/4h

Butyl acetate

LD₅₀ (rat, ingestion) 14000 mg/kg
LC₅₀ (rat, inhalation) 9660 mg/m³ /8h

1-methoxy -2-propanol acetate

LD₅₀ (rat, ingestion) 8532mg/kg**b) Irritating effect**

Skin: irritating to skin and mucous membrane

Eyes: irritating effect

c) Caustic effect

Mixture is not classified as caustic. No available data confirming the hazard class.

d) Allergic effects

Mixture is not classified as allergenic. No available data confirming the hazard class.

e) Toxicity for repeated exposure

Repeated exposure may cause skin dryness or cracking.

f) Cancerogenity

Mixture is not classified as cancerogenic. No available data confirming the hazard class.

g) Mutagenity

Mixture is not classified as mutagenic. No available data confirming the hazard class.

**ACRYL FILLER 5+1 HS Q-2002****h) Harmful effect on reproduction**

Mixture is not classified as harmful to reproduction. No available data confirming the hazard class.

Exposure methods:

Respiratory tract: Harmful in case of inhalation.

Skin: Harmful to skin.

Eyes: Irritating to eyes.

If swallowed the substance may cause irritation of the alimentary tract, nausea, vomiting and diarrhea.

Poisoning symptoms:

Headaches and dizziness, fatigue, decreased muscle power, drowsiness and in exceptional instances loss of consciousness. Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

SECTION 12: ECOLOGICAL INFORMATION

No experimental data available on the preparation. Evaluation based on the data on dangerous ingredients included in the preparation.

12.1. Toxicity

1-metoxy -2-propanol acetate

Daphnia magna /EC50 (48 hours) > 500 mg/l

Oncorhynchus mykiss /LC50 (96 hours) 100-180 mg/l

Number in catalogue of water hazardous substances: 5033

Water hazard class: 1

Xylene

Daphnia magna /EC50 (48 hours) 7,4 mg/l

Acute toxicity for mammals: 3; for fish: 4,1

Number in catalogue of water hazardous substances: 206

Water hazard class: 2

Butyl acetate

Number in catalogue of water hazardous substances: 42

Water hazard class: 1

12.2. Persistence and degradability

Butyl acetate

Biodegradability: 98% (close bottle test)

12.3. Bioaccumulative potential

Butyl acetate

Biodegradation coefficient: BCF=3,1

12.4. Mobility in soil

Very poorly soluble in water.

12.5. Results of PBT and vPvB assesment

No data available.

12.6. Other hazardous effects

No data available

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Product must be disposed of in compliance with the proper local and statutory regulations with regard to waste – see point 15.

Product remains:

Waste code: 08 01 11* Do not dispose the product into the sewage system. Do not store with communal waste.

**ACRYL FILLER 5+1 HS Q-2002**

Remove the remains of the mixture carefully and harden with the use of the proper B component, a (waste) hardener from the set. Hardened product is not harmful waste.

CAUTION: harden the remains in small portions away from flammable products. High amounts of heat are released during chemical reaction!

Contaminated container:

A contaminated container containing unhardened remains of the product is harmful waste. Waste code: 15 01 10*. Do not store with communal waste. The contaminated container should be disposed with entities which are authorized to collection, recover o disposal.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class (es)

3

14.4. Packaging group

III

14.5. Environmental hazards

no

14.6. Special precautions for user

Do not transport together with products of class 1 (except products of class 1.4S), and some products of class 4.1 i 5.2. During the transport avoid direct contact with products of class 5.1 i 5.2. Do not use an open flame and do not smoke.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 Convention and the IBC Code

Not applicable.

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations / legislations specific for the substance or mixture**

- Directive 67/548 /EWG (2006/121/WE)
- Directive 91/155/EWG (2001/58/WE)
- Directive 1999/45/EC (2006/8/WE)
- REACH – Regulation 2006/1907/WE
- CLP – Regulation 1272/2008/WE

15.2. Chemical safety assessment

Not performed

SECTION 16: OTHER INFORMATION**16.1. Full text of the phrases identifying the types of hazards and R phrases mentioned in sections 2-15:**

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Flam.Liq.3

H226 Flammable liquid and vapour

STOT SE 3 Toxic effect on target organs – single exposure, cat. 3

H336 May cause drowsiness or dizziness

Acute Tox.

H332 Harmful if inhaled



ACRYL FILLER 5+1 HS Q-2002

H312 Harmful in contact with skin.

Skin Irrit. 2

H315 Causes skin irritation category 2

EUH066 Repeated exposure may cause skin dryness or cracking

16.2. Explanations of the abbreviations and acronyms used in the Material Safety Data Sheet:

Nr CAS – numerical symbol ascribed to a chemical substance by the American organization Chemical Abstracts Service (CAS).

Nr EC – a number ascribed to a chemical substance in the European List of Notified Chemical Substances (ELINCS), or a number in the European Inventory of Existing Chemical Substances mentioned in "No-longer polymers" publication (EINECS)

MPC – maximum permissible concentration of health hazardous substances in the work place.

MPIC – maximum permissible instantaneous concentration.

MPCC – maximum permissible ceiling concentration.

PCB – permissible concentration in biological material

UN number – four-digit identification number of a substance, preparation or product pursuant to UN model regulations

Information based on our current knowledge. This document does not guarantee the product characteristic.

Classification of the mixture is based on classification rules contained in directive 1999/45/WE.

Changes: general update