

TECHNICAL DATA SHEET**Silicone remover**

Mixture of organic solvents. This product effectively removes all types of contamination including grease and silicone remaining on metal and coated surfaces.

This product is intended to remove such contamination as: silicone, teflon, oil and grease from surfaces intended to be lacquered.

It can be used on:

- steel surfaces
- aluminium surfaces
- galvanized steel
- stainless steel
- old paint coats
- acrylic fillers
- putties and filling coats
- plastics

Instruction for use:

Apply the product on a cloth (or other type cleaning wiper) and remove all contamination remaining on the surface of cleaned substrate. Immediately after the application of the product on the surface dry the surface with another piece of clean and absorptive cloth. It is necessary to change the cloth frequently and regularly.

Content of volatile organic compounds:

Maximum content of VOC in the product: 740 g/l
VOC II/B/a limit= 850 g/l

Storage conditions:

Store in a dark and cool place away from fire and heat sources. The shelf life in original package in the temperature of 20°C is 24 months.

TECHNICAL DATA SHEET**Health and safety recommendations:**

According to Material Safety Data Sheet of Dangerous Substance for particular product.

Packaging:

Art. No	Capacity	Package, pieces:	Weight of carton, kg:
40504	1l	6	6,20
40505	5L	4	20,00

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.

RANAL Sp. z o.o.