

# Universal thinner for acryl products RANAL

## **Description:**

This thinner designed for acryl products is a mixture of organic thinners, which results in a product with definite evaporation temperatures. It is designed for thinning acryl lacquers, metal bases and fillers in order to receive the required density before applying on the painted elements of a car body. Evaporation time can be shortened or extended by choosing the appropriate thinner: standard, guick or slow. Standard thinner is especially recommended for works in the temperatures between 20 and 25°C. The quick one is recommended for large surfaces repairs in the temperature of 20°C and for minor repairs. Slow thinner is especially recommended for the repairs in the temperature exceeding 20-25°C.

### Can be applied with:

Acryl fillers, clear acryl lacquers (also ECO), acryl enamels and metal bases.

### Mixing ratio:

Apply technical data sheet of a thinned product.

#### Colour:

Clear

#### Storage:

To be stored in dry and cool place, away from the sources of light and heat. Avoid sun exposure. Storage time of the product in the original package in the temperature 20°C is equal to 24 months.

### Health and safety recommendations:

Apply safety data sheet of the particular product.

### Packaging:

Art.Nr	Capacity, L:	Package, pieces:	Weight of the carton, kg
40101-1	1,0	6	6,00
40102-1	5,0	4	4,60

This information is based on careful, laboratory research and our long-standing experience. Strong market position does not absolve us from constant control of the quality of our products. However, we are not responsible for the final results after incorrect use of the product.

RANAL Sp. z o.o.